

## Description

# [Insert title of invention]Single Towing Device for both Car and Cart

### BACKGROUND OF INVENTION

- [0001] This invention relates generally to the art of towing devices and more particularly those which allow a vehicle to be towed. 1. Background In today's world, there are a large number of people who are traveling in Recreation Vehicles (RV); this is especially true of older and retired members of society.
- [0002] Many people who use RVs park them at camps and camping sites, sometimes over night and sometimes for months at a time. Many of these camps are large with little means of transportation so many people bring and use golf carts or similar devices for transportation. This can also be true of a motorcycle, four wheeler or Jet Ski depending on the park and the type of usage desired.
- [0003] For many RV owners there is also a need for an alternative vehicle; as the RV is not convenient for going to the store

or for various day trips. When an RV is at a site it is usually connected to that site's water and power sources making it a burden to unhook. Therefore many RV owners tow a car, truck or other vehicle behind the RV as a means of transportation outside of the camping site.

[0004] Many RV owners want both their car and their cart with them without having to use a full sized trailer or having someone else transport the golf cart for them.

[0005] Ideally, an RV can tow a golf cart or a similar device and a vehicle; however there is no device that can easily accommodate both. The lack a device that can easily and safely handle both a cart and an automobile, shows that there is still room for improvement in the art.

## **SUMMARY OF INVENTION**

[0006] The present invention relates to a towing device which utilizes a towing base, wheels, and a plurality of movable tracks, a tongue hitch attachment, and a vehicle locator swivel plate. The invention can be supplied with hydraulic surge brakes or electric brakes as well as brake and turn lights. Tie down straps are used for securing the vehicle to the dolly.

[0007] The invention features an adjustable car locator swivel plate. This allows the adjustment of the weight distribu-

tion to "fine tune"the load. The tongue weight can be adjusted to comply with the RV hitch"s requirements. Using the loading ramps supplied with the invention, the automobile and the golf cart can be ready for transport quickly and easily.

[0008] Accordingly, it is an object of the present invention to provide a towing device that allows for the easy and safe towing of a vehicle and a device like a golf cart, Jet Ski or motorcycle. It is another object of the present invention to provide a towing device that has moveable tracks so that it can be used to support and tow many different devices.

[0009] These, together with other objects of this invention, along with various features of novelty which characterize this invention, are pointed out with particularity in the claims annexed hereto and forming a part of this disclosure. For a better understanding of this invention, its operating advantages and the specific objects attained by its uses, reference should be had to the accompanying drawings and descriptive matter in which is illustrated in the preferred embodiment.

#### **BRIEF DESCRIPTION OF DRAWINGS**

[0010] Without restricting the full scope of this invention, the preferred form of this invention is illustrated in the fol-

lowing drawings:

- [0011] FIG 1 shows a top front view of the main components of the device;
- [0012] FIG 2 displays a bottom side view of the main components of the device;
- [0013] FIG 3 shows a view of the hitch tongue of the device;
- [0014] FIG 4 displays the vehicle locator swivel plate;
- [0015] FIG 5 displays a golf cart being loaded on the movable racks;
- [0016] FIG 6 displays the movable racks;
- [0017] FIG 7 displays the bolting rack attachment means;
- [0018] FIG 8 displays the use of a movable rack with a motorcycle;
- [0019] FIG 9 shows the device towing a car and a golf cart; and
- [0020] FIG 10 shows a top perspective front view of the main components of the device.

#### **DETAILED DESCRIPTION**

- [0021] The following description of a towing device is demonstrative in nature and is not intended to limit the scope of the invention or its application of uses.
- [0022] The present invention relates to a towing device 1 which

utilizes a towing base, wheels, and a plurality of movable tracks, a tongue hitch attachment, and a vehicle locator swivel plate. The invention can be supplied with hydraulic surge brakes or electric brakes as well as brake and turn lights. Tie down straps are used for securing the vehicle to the dolly.

[0023] As shown in Fig. 1, Fig. 2 and Fig. 10, the device has a towing base 100 which is comprised of a main support beam 25 which runs parallel to the Motor Home 400. The main support beam 25 is attached to a wheel axis support 95. The wheel axis support 95 is perpendicular to the main support beam 25 and attached through an attachment means such as welding. The towing base 100 has a plurality of angled supplemental support beams 90 that are attached to the towing base 100 and the wheel axis support 95 at a 45 degree angle. The angled supplemental support beams 90 add additional support to the towing base 100.

[0024] The towing base 100 has a rack support base 35. The rack support base 35 is rectangular in shape. The rack support base 35 is attached to the support beam 25 and extending out an equal distance from the support base 25, two feet in the preferred embodiment parallel with the wheel

axis support 95 and perpendicular to the main support beam 25. The rack support base 35 then turns at a 90 degree angle towards and connects to the wheel axis support 95. The rack support base 35 is symmetrical to the support beam 25 for maintaining a stable load balance. The rack support base 35 provides the support structure for the movable racks 45.

[0025] As shown in Fig. 3, connected to the support beam 25 and the opposite end of the wheel axis support 95 is the tongue hitch attachment 15. The tongue hitch attachment 15 is used to attach the device 1 to the hitch of the RV 400 or other vehicle that is towing it. Tongue hitch attachments 15 are well known in the art and are not disclosed here in great detail. The tongue hitch attachment 15 has a socket that locks on the ball of the hitch 215. This allows the device 1 to turn separately from the RV 400. The tongue hitch attachment 15 has a tongue weight which can be adjusted to comply with the RV hitch's 215 requirements. The tongue weight of the device 1 must be in compliance with the Rated Hitch Capacity of the Tow Vehicle. The tongue weight is adjusted by moving the Swivel Plate location with the series of adjustment holes provided, which shifts weight towards or away from the

tongue of the device 1. When making this adjustment, the pivot bolt and nut must be tightened to a point of having at least 3 threads of the end of the bolt exposed past the nut. The nut is a self locking style, and should always be stiffly rotating, if not, it must be replaced before using the device 1.

[0026] The wheel axis support 95 is connected to a plurality of wheels 55. There are two wheels 55 in the preferred embodiment, one on each side of the wheel axis support 95 and parallel to the support beam 25. The wheels 55 are attached to the wheel axis support 95 using a typical axle/ball bearing configuration. The wheels 55 add the mobility for the device 1. In the preferred embodiment, each wheel 55 is covered by a wheel fender 65 which is in a hollow half moon shape that covers the top of the wheel 55 and is attached to the wheel axis support 95. The fender 65 would be full fenders with inner liners. In the preferred embodiment the wheels 55 have tires that are 205/75R 14" Radial 6Ply Rated Trailer Tires–1760lb Load Rating each.

[0027] The device 1 can be supplied with a braking system 125 of the wheels 55. This braking system can be with hydraulic surge brakes or electric brakes 125. A brake cable 225

runs from the RV 400 to the device 1 to activate the brakes 125. The device 1 can also have turn signals and/or reflector lights.

[0028] The invention features an adjustable car locator swivel plate 75. This allows the adjustment of the weight distribution to "fine tune" the load. The adjustable car locator swivel plate 75 is slightly behind the wheels 55 in the direction opposite from the tongue hitch attachment 15. The car locator swivel plate 75 is on a pivot that allows for the adjustment of weight distribution. The locator swivel plate allows for Multiple Position Car Locator for correct balance. The location of the locator swivel plate 75 on the device 1, right behind the wheels 55 allows for the base distribution and the most efficient bearing of the load of the car weight. The vehicle locator plate 75 is used to locate, support and restrain the front wheels 55 of the towed vehicle 200. As shown in Fig. 4, the vehicle locator plate 75 is retained on the device by one large (pivot) bolt 71 in the center of the width and length of the plate 75. This bolt 71 is the point of rotation for the car 200 in tow as the dolly follows the RV 400 through the radius of a turn. In the current invention, the locator plate 75 can be re-positioned through a series of hole positions 72 in a

fore & aft member that is connected to the base 100 that allow it to be either closer or further from the device 1 axle position. The device's 1 axle acts as the balance point for the golf cart 300 towards the front of the device 1, and the towed vehicle 200 towards the rear. By moving the locator plate 75 which moves the towed vehicle closer to the device 1 axle,(forward) or away from the axle(rearward), weight distribution can be directed towards the hitch or away from the hitch, allowing the operator to adjust their load distribution between the hitch 215 and the wheels 55.

[0029] As shown in Fig. 5, the loading ramps 215 are used to load the automobile 200 and the golf cart 300 for transport in a quick and easy manner.

[0030] Fig. 6 shows the movable racks 45. The movable racks 45 are in a long rectangular shape wide enough for a standard golf cart tire to fit and approximately 102" in length in the preferred embodiment. The movable rack 45 has a lip 41 of two inches on each of its elongated sides. The short ends of the movable rack 45 are open to allow the loading and unloading of the golf cart 300 or other vehicle. Having both ends allow the the golf cart 300 or other secondary vehicle can load from either side of the device

1. This is advantageous in busy and crowded parks.

[0031] In an alternative embodiment, the movable racks 45 can have a wheel chock 42 on one of the short sides which is used to secure the golf cart 300 or other vehicle and to make sure that the golf cart 300 does not go past the end of the movable racks 45.

[0032] The movable racks 45 are connected to the rack support base 35 through a connecting means as shown in Fig. 7. In the preferred embodiment, the connecting means is the use of pairs of attachment walls 42 that extend from the bottom of the movable racks 45. Each pair of attachment walls 42 are spaced apart with enough distance between them that they line up on either side of the beam 49 of the rack support base 35. In the preferred embodiment there are two beams 49 that form the rack support base 35. The attachment walls 42 are perpendicular to the elongated sides of the movable racks 45. The attachment walls 42 have a plurality of holes 46 that line up with a series of holes 47 in the beams 49 of the rack support base 35. An attachment means such as a bolt and lock pin 48 are used to secure the movable racks 45 to the rack support base 35.

[0033] The movable racks 45 can be attached to the proper beam

holes 47 that are best for the load to be loaded. This allows for adjustment of the movable racks 45 to best fit to load. For a standard golf cart 300, two movable racks 45 will be used, but only one or more than two movable racks 45 can be used depending on the load. Fig. 8 demonstrates the use of only one movable rack 45 for use with a motorcycle 500. The device 1 can be used with a motorcycle, ATV, Jet Ski or other similar device.

[0034] Because RV site space is so limited, the device in the preferred embodiment fits within an area just 30" longer than a standard tow dolly. This will allow a user to tuck the device 1 up under the rear of a standard motor home 400 to save space.

[0035] An Attachment means, such as tie down straps 135 are used to secure the vehicle 200 and golf cart 300 to the device 1.

[0036] In the preferred embodiment the device 1 would have a 3500 lb Load Rating and a High Gloss Polyester Powder Coated Finish. In the preferred embodiment, the device 1 is made of a strong, durable but light weight material such as stainless strength steel with the parts molded and welded together using standard welding practices.

[0037] Having described the fundamental components and func-

tions of an embodiment, details of the same are now described with greater specificity.

[0038] *Operation*

[0039] Fig. 9 shows the device 1 load with a vehicle 200 and a golf cart 300 being towed by a Recreation Vehicle 400. It shows the fastening means, such as the tie down straps 135 for fastening the towed vehicles to the device 1. The device 1 must be securely hitched to the tow vehicle 400 before loading. While Fig. 10 shows a prospective front view of the device 1 with the alternative embodiment of having the movable racks 45 having wheel chocks 42. Since the golf cart 300 or other secondary vehicle is transported crossways, it must measure less than 102 inches in length in order to comply with maximum width limits for highway use. The removal of rear facing seats, foot rests, or other accessories may be necessary.

[0040] Although many features, functions, and advantages of the present invention have been described in this specification, together with details of the structure of specific embodiments thereof, the description as a whole is illustrative only, and substitutions may be made in detail, especially in matters of shape, dimension and arrangement of elements within the principles of the invention to the full

extent indicated by the broad, general meaning of the terms in which the claims are expressed.

[0041] *Advantages*

[0042] The previously described version of the present invention has many advantages, including many elements missing in all prior art.

[0043] Although many features, functions, and advantages of the present invention have been described in this specification, together with details of the structure of specific embodiments thereof, the description as a whole is illustrative only, and substitutions may be made in detail, especially in matters of shape, dimension and arrangement of elements within the principles of the invention to the full extent indicated by the broad, general meaning of the terms in which the claims are expressed. Therefore, the point and scope of the appended claims should not be limited to the description of the preferred versions contained herein.